ChoreMaster® Series

3600, 6000 & 8000-Watt - Gasoline







All Models

NEMA I 14-30B 120V/240V GEN-8000 Models

Featuring 3600, 6000 and 8000-watt generators, the ChoreMaster Series come with a Mi-T-M OHV engine and are designed to provide maximum power for contractors and electrical back-up for power outages.

Alternator:

Total harmonic distortion (THD) less than 6% Copper and aluminum windings

Low profile, compact design | Powder coated wraparound frame with 1-inch steel tubing

Components:

Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles Large low tone mufflers | Engine on/off switch | Fuel shut-off valve | DC/battery charging

Limited Warranties:

1 year alternator | 1 year Mi-T-M engine

Certification:

CSA Certified



MODEL NO. GEN-3600-0MM0 GEN-6000-0MM0 GEN-8000-0MME 3600 watts 6000 watts 8000 watts MAX. AC OUTPUT 3000 watts 5500 watts 7000 watts RATED AC OUTPUT DISPLACEMENT/ENGINE 212cc Mi-T-M OHV 389cc Mi-T-M OHV 420cc Mi-T-M OHV with electric start - battery included Brushed 120V, 60Hz Brushed 120V/240V, 60Hz Brushed 120V/240V, 60Hz **ALTERNATOR** 30.0 50.0/25.0 66.6/33.3 MAX. AMPS (120V/240V) CONT. AMPS (120V/240V) 25.0 45.8/22.9 58.3/29.2 (2) 120V, 20A GFCI duplex (2) 120V, 20A GFCI duplex (2) 120V, 20A GFCI duplex RECEPTACLES (1) 120V, 30A twist lock (1) 120V, 30A twist lock (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock (1) 120V/240V, 30A twist lock (1) Main circuit breaker (1) Main circuit breaker (1) Main circuit breaker CIRCUIT BREAKERS (2) 20A circuit breakers, single pole (2) 20A circuit breakers, single pole (2) 20A circuit breakers, single pole (1) 10A DC breaker (1) 10A DC breaker (1) 10A DC breaker 3600 RPM 3600 RPM 3600 RPM RATED SPEED DECIBEL RATING 72.0 74.0 74.0 4.0 gallons 6.6 gallons 6.6 gallons FUEL CAPACITY 8.5 hours 6.5 hours 6.0 hours RUN TIME (AT FULL LOAD) IDLE CONTROL No No Yes, includes tires and rubber gripped handles Yes, includes tires and rubber gripped handles WHFFI KIT DIMENSIONS (LxWxH) 24.9x17.6x17.9in. 39.1x28.7x30.6in.* 39.1x28.7x30.6in.* SHIP WT. 134 lb. 237 lb. 102 lb. 180 lb. 195 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

Dimensions include the wheel kit with the handles in the down position.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adapter	All models	AW-6000-1002	Equipment cover	6000 & 8000-watt
AW-5090-0009	Lifting hook	GEN-3600-0MM0			models