Portable Generators

6000-Watt - Diesel



Alternator:

Total harmonic distortion (THD) less than 5% | 100% copper windings

Frame:

Heavy-duty powder coated wraparound frame with 1-inch steel tubing | Angled isolator design features six neoprene isolators

Components:

Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
Fuel shut-off valve
Easy-to-read fuel gauge
Voltmeter/hour meter
Heavy-duty industrial air cleaner

Limited Warranties:

2 year alternator | 3 year Kohler engine

Certification:

CSA Certified



Portable gasoline generators tend to be the most popular among contractors, but this portable diesel generator provides heavy-duty power for long life and extended operation. Plus, it costs less to operate than it's gasoline counterparts.

MODEL NO.
MAX. AC OUTPUT
RATED AC OUTPUT
HORSEPOWER/ENGINE

GEN-6000-0MKD 6000 watts 5000 watts

GINE 9.1 HP Kohler KD440 OHV with electric start - battery included

ALTERNATOR Brushless 120V/240V, 60Hz

MAX. AMPS (120V/240V) 50.0/25.0 CONT. AMPS (120V/240V) 41.7/20.8

RECEPTACLES (2) 120V, 20A GFCI duplex

(1) 120V/240V, 20A twist lock

(1) 120V, 30A twist lock
(1) Main circuit breaker

(2) 20A toggle circuit breakers, single pole (1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole

RATED SPEED 3600 RPM

DECIBEL RATING 85.0

FUEL CAPACITY 2.6 gallons

RUN TIME (AT FULL LOAD) 6.8 hours

DIMENSIONS (LxWxH) 29x21.62x22.5in.

SHIP WT. 295 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

273 lb.

Accessories:

NET WT.

PART NUMBER	DESCRIPTION	FITS MODEL	PART NUMBER	DESCRIPTION	FITS MODEL
32-0915	RV generator adapter	GEN-6000-0MKD	AW-5740-0006	Wheel kit with flat-free tires	GEN-6000-0MKD
AW-5090-0007	Lifting hook	GEN-6000-0MKD	AW-6000-1002	Equipment cover	GEN-6000-0MKD





14-20R NEMA L5-30R 240V 120VAC