



BOOSTER

MODEL	: 530		
INTENDED USE	: Compressed Air/Gas		
INPUT PRESSURE	: 115 psi (8 Bar)		
WORKING PRESSURE	: 580 psi (40 Bar)		
CAPACITY	: 2800 l/min	3800 l/min	4800 l/min
MOTOR POWER	: 11 kW (15 Hp)	15 kW (20 Hp)	18,5 kW (25 Hp)
COMPRESSOR SPEED	: 900 rpm	1080 rpm	1200 rpm
NUMBER OF STAGE	: 1		
NUMBER OF CYLINDER	: 3		
LUBRICATION SYSTEM	: Forced Lubrication		
POWER TRANSMISSION	: Belt-Pulley		
WORKING TEMP. RANGE	: 32...122 F (0...+50 C)		
DIMENSIONS (WxLxH)	: 34 x 30 x 52 inches		
WEIGHT	: 930 lbs.	940 lbs.	950 lbs.

STANDARD EQUIPMENT

Intercooler

Pressure Switch for Automatic Start/Stop

Safety Valve at Each Stage

Automatic Drain Solenoid

Oil Level Switch

Oil Level Sight Gauge

Electrostatic Painted Chassis

Manometers for Stage Pressures

Thermal Overload Protection for Electric Motor

Shock Mounts

OPTIONAL

PLC Touch Screen Control System

Stainless Chassis