

130 cfm Hydraulic Driven Rotary Screw Compressor



130 cfm @ 100 psi

125 cfm @ 150 psi

Features

- All hydraulic fluid and air connections on same side
- ASME/CRN certified safety valves
- CAS SMART fluid control system
- Compressor load/unload operation
- Easy to remove compressor cover
- External NEMA 4 on/off switch
- Heavy-duty industrial rotary screw airend
- Hydraulic fluid flow regulator
- Hydraulic fluid pressure regulator
- Hydraulic fluid bypass valve
- Intake filter silencer
- NEMA 4 load/unload switch
- Steel mounting plate
- Vibration mounting pads
- 12 volt compressor air & oil cooler pack*
- 12 volt control system**



Package Options

- Cold weather heating package
- Cover color change
- High ambient temperature cooling package
- Hose reels
- Hydraulic fluid cooler
- Tank mounted
- 24 volt operation
- 110 volt operation

* Cooler pack to be mounted external to compressor system. 12 volt control voltage connection to be supplied by vehicle/equipment compressor is mounted to.

Do not let hydraulic fluid exceed 190 F°



Model	cfm @ 100 psi	cfm @ 150 psi	Hydraulic psi Required	GPM Hydraulic Flow Required	Length	Width	Height
H-BM125RS	65	60	2250	20	34	20	28

Dimensions are representatives of package dimensions not total space required for mounting.

No Start Up Kit Required

Optional 5-year Pump Warranty Available

See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 3-2019

