

20 HP Duplex



Basic Compressor Features


- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-groove B width motor pulley
- 2-piece tank top plate design

Elite Compressor Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

**150 cfm @ 175 psi
(Time Delay)**

**75 cfm @ 175 psi
(Alternating)**



Air cooled after cooler on Elite unit



| Model | Voltage | Tank | Elite/Basic | Length | Width | Height |
|---|-----------------|------------|-------------|--------|-------|--------|
| DB203H249 | 208-230/460-480 | 240 Gallon | Basic | 85 | 52 | 72 |
| Add -E to model number to make Elite Unit | | | | | | |

No Start Up Kit Required

Optional 5-year Pump Warranty Available

See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 6-2019

