


# AIR N ARC® 300 HYDRAULIC



www.CompressedAirSystems.com

## Five Forms Of Power – One Unit, Hydraulically Driven

The Air N Arc® 300 Hydraulic All-In-One Power System® features the innovation of being hydraulically driven, while still offering all the advantages of the Air N Arc® 300 engine drive system including a 40 CFM rotary screw air compressor, 300 AMP welder, 300 AMP 12V charger and 12V/24V booster, and 7 kW generator. Designed as a true two generator system, the Air N Arc® 300 Hydraulic allows simultaneous dual functionality such as welding and generator for lights for nighttime service. The system offers a small footprint for side pack or behind-the-cab mounting and is ideal for trucks with hydraulics already installed, such as crane trucks.

### SPECIFICATIONS

<b>Drive System</b>	Open Center Hydraulic
<b>Hydraulic Requirements</b>	19 GPM @ 2800 PSI Multifunction/14.5 GPM @ 2500 PSI Single function
<b>Air Compressor</b>	Rotary Screw, 40 CFM, 175 PSI
<b>Generator</b>	7 kW Peak - 6.8 kW Continuous, AC Power, 60 Hz, Single Phase, 120V and 240V Outlets
<b>Welder</b>	High Frequency DC Welding, 270 AMPs at 100% Duty Cycle CC: 40-300 AMPs Operating Range, CV: 15-30 Volts
<b>Battery Booster/Charger</b>	300 AMPs 12V/24V Boost, 50 AMP 12V Charge

Dimensions with fittings (In.):  
48.7L X 21W X 30.9H | Dry Weight with Control Panel (Lbs.): 621

\* Ratings are approximate and are based on 120 °F hydraulic fluid temperature. Add 400 PSI minimum to hydraulic requirements for hydraulic system continuous pressure ratings. Consult Vanair® for specific details.

Product improvement is a continuing goal. Design and specifications are subject to change without notice or obligation.  
AIRNARC300H\_12082017



#### **SPECIAL FEATURES**

- Single Function 14.5 GPM Model is Suitable for Ford® 4X4 Super Duty and Dodge® Trucks
- True Two Generator System for Safe Multi-function of Welder and Electric Tools
- Small Footprint - Will Fit on Side Pack or Behind Cab
- Integrated Hydraulic Cooler
- CV MIG Capability
- One Unit to Start all Your Equipment with Battery Charge and Boost Capability
- Rotary Screw Air Compressor for Air on Demand
- Heavy Duty Belt Drive System for Anti-vibration and Long Service Intervals
- Integrated Lift Hook
- Designed with Hinged Lid for Easy Maintenance
- Powder Coated Sheet Metal
- Galvannealed Steel

#### **AIR COMPRESSOR**

- Rotary Screw Compressor - Encapsulated
- 40 CFM @ 150 PSI
- 175 Max PSI

#### **WELDER**

- High Frequency DC Welding
- 270 AMPS at 100% Duty Cycle
- CC Range 40 – 300 AMPS Operating Range
- CV Range 15 – 30 Volts
- Independent DC Welder
- Safe Multi-Function

#### **GENERATOR**

- 7 kW Peak
- 6.8 kW Continuous @ 60 Hz
- Independent AC Power for Safe Multi-functioning
- Brushless
- Smooth Wave for Minimal Distortion
- Two-120V Outlets and One-240V Outlet

#### **BATTERY BOOST/CHARGE**

- 300 AMP 12V/24V Boost
- 50 AMP 12V Charge

#### **REMOTE CONTROL PANEL**

- Provides Ultimate User Convenience and Safety
- All Functions Accessible at Panel. No Need to Jump In and Out of Vehicle.

#### **OPTIONS/ACCESSORIES**

- Welding Cables - 25', 50'
- Welding Helmet with Auto Darkening Lens
- Battery Booster Cables
- Cable Extension Segment
- Remote Air Tank – 30 Gallon
- Remote Condensation Drain
- Maintenance Kits
- Welding Rods
- Compressor Air Inlet Heater
- Hose Reels and Fittings
- OSHA Safety Valve (Velocity Fuse)
- Post Drivers
- Service/Control Line Moisture Separators
- Tool Oiler/Lubricator

#### **HYDRAULIC SYSTEM REQUIREMENTS**

All hydraulic ratings and pressures are at the machine and do not take into account the pressure drops of individual hydraulic systems. These pressure drops need to be taken into account and added to the rating of the hydraulic pump and components. Vanair highly recommends consulting a hydraulic supply expert for specifying the correct hydraulic pump size and type, oil reservoir size, hydraulic cooler, hydraulic pressure relief, and other hydraulic supply components for your application. Please take into consideration the following: The hydraulic flow and pressure requirements of the air compressor, the continuous hydraulic load when the compressor is running, the duty cycle and ambient operating temperatures, and any other hydraulic equipment that may share the same hydraulic supply system (Vanair recommends a dedicated pump and hydraulic circuit).