

E4-20-C-E3 Compressor

- ❖ 24 CFM
- ❖ 6000 PSI
- ❖ 20 HP ELECTRIC MOTOR
- ❖ Three Phase Electric
- ❖ 49" h. x 29" d. x 49" w.
- ❖ Weight: 900 lbs. approx.



SPECIFICATIONS

COMPRESSOR

The compressor block is 4 stage, air cooled, pressure lubricated, has inter coolers and after cooler, relief valves on all stages, and a multi-blade flywheel fan to provide high velocity cooling over the compressor. Standard equipment includes an auto-drain system, hour meter, high-pressure shut down, carbon-monoxide visual indicator and a deluxe cabinet enclosure including a gauge panel.

PURIFICATION

It comes with a two cartridge filtration system rated at 57,000 Cu. Ft. of air capacity at 80°F. The system uses a dryer bed to remove water in excess of dew point -65 degrees. (NFPA 1500 standard) Activated charcoal and a carbon monoxide catalyst remove remaining contaminants to provide CGA Grade "E" breathing air.

ELECTRICAL REQUIREMENTS

The minimum requirement for three-phase operation is a 50 Amp, 230 or 208 Volt connection.

North Shore Compressor & Machine, Inc

83 Outer Drive, Silver Bay, MN 55614 (218) 226-4695

www.northshorecompressor.com

800-526-6395

(218)-226-3440 Fax

email: info@northshorecompressor.com