



CLEMCO
The Performance System

TECHNICAL DATA SHEET

Note: For safe, efficient blasting, read and follow the owner's manual and seek training for everyone who will use this equipment.

Purpose

The Clemco nylon quick coupling nozzle holders attach to any blast hose fitted with quick couplings and hold the blast nozzle in place during blasting.

Description of Operation

The operator uses a quarter turn to attach the quick coupling to any blast hose fitted with standard blast hose quick couplings. A lock-spring on the nozzle holder keeps the holder from coming uncoupled when attached to any Clemco coupling. The coupling gasket serves as the nozzle washer.

Nozzles

- FHP accepts a 1 1/4-inch entry flanged nozzle
- CFP accepts a 1-inch entry, 1 1/4-inch thread nozzle
- CFPM accepts a 1-inch or 1 1/4-inch entry contractor thread nozzle

Advantages

- Fiber-reinforced nylon material springs back from most impacts that would dent or deform metal couplings
- Built-in lock-springs eliminate need for safety pins
- Quick coupling holders can attach to any coupled hose, simplifying blast hose inventory
- Lighter weight than metal nozzle holders

Description

Fiber-reinforced nylon quick coupling nozzle holder for abrasive blast cleaning.

Quick Coupling Nylon Nozzle Holders

Stock No. CFPM-07716, CFP-07718, FHP-07719



CFPM Nozzle Holder, Stock No. 07719
(For contractor thread nozzles)
Shown with optional nozzle



CFP Nozzle Holder, Stock No. 07716
(For 1 1/4" thread nozzles)
Shown with optional nozzle



FHP Nozzle Holder, Stock No. 07718
(For flanged nozzles)
Shown with optional nozzle

Related Clemco Literature

Description	Stock No.
Contractor Series Catalog	21385
Abrasive Blasting Safety Practices	22090
Blast Off 2	09294

Options & Accessories

Description	Stock No.
Coupling Gaskets (10) (for CFP and CFPM)*	08853
*Not included with the FHP. Nozzle washer serves as coupling gasket.	

Color

Yellow

Packaging

Ships loose

Dimensions	Unit
Height:	2 1/2"
Width (dia.):	3 3/8"
Weight:	.25 lb

(Dimensions are the same for all models)

Authorized Distributor:

ISO 9001-2000 certified. Clemco is committed to continuous product improvement. Specifications are subject to change without notice.