



HIGH PRESSURE AIR COMPRESSOR

MODEL	: W32 - CANOPY BOOSTER		
INTENDED USE	: Compressed Gas		
FILTER SYSTEM	: P41		
WORKING PRESSURE	: 3260 psi (225 Bar)		
MAX. WORKING PRESSURE	: 5000 psi (350 Bar)		
CAPACITY	: 250 l/min	: 300 l/min	: 350 l/min
MOTOR POWER	: 4 kW (5,5 Hp)	: 5,5 kW (7,5 Hp)	: 7,5 kW (10 Hp)
COMPRESSOR SPEED	: 1250 rpm	: 1350 rpm	: 1500 rpm
1st STG PRESSURE RANGE	: 70 - 290 psi (5 - 20 Bar)		
2nd STG PRESSURE RANGE	: 290 - 870 psi (20-60 Bar)		
3rd STG PRESSURE RANGE	: Outlet Pressure		
NUMBER OF STAGE	: 3		
NUMBER OF CYLINDER	: 3		
LUBRICATION SYSTEM	: Forced Lubrication		
POWER TRANSMISSION	: Belt-Pulley		
WORKING TEMP. RANGE	: 32...122 F (0...+50 C)		
DIMENSIONS (WxLxH)	: 28 x 40 x 51 inches		
WEIGHT	: 620 lbs.	: 640 lbs.	: 660 lbs.

STANDARD EQUIPMENT

P41 Purifier and Refillable Cartridge

2nd and 3rd Stage Water Separator

Intercooler , Aftercooler

Priority Valve , Check Valve

Safety Valve at Each Stage

Oil Level Glass - Oil Level Switch

Shock Mounts

Manuel Start - Stop - Drain

Thermal Overload Protection for Electric Motor

Control Panel: On Off Buttons, Hour Counter

Electrostatic Painted Chassis

OPTIONAL

Automatic Start - Stop - Discharge

Stainless Chassis

Replaceable (Disposable) Cartridge