

PDS400S-6E1400 cfm

AIRMAN air compressors are manufactured to the highest quality, consistently delivering the industry's best return on investment.

ANA is committed to supplying the finest products with unmatched performance and support, maintaining their value over time.

- 400 cfm Free Air Delivery
- Best-in-Class Fuel Efficiency
- Kubota Diesel Engine
- EPA Tier 4F & CARB Compliant





Alliance North America

Phone: 562-450-3570 E-mail: sales@anacorp.com

www.anacorp.com

California: 12311 Industry St. • Garden Grove, CA 92841
Texas: 10440 Brockwood Road • Dallas, Texas 75238
South Carolina: 4220 S. Church St. • Roebuck, SC 29376

© COPYRIGHT 2020, ANA • 020420 AIRMAN is a trademark of HOKUETSU INDUSTRIES CO., LTD.

Features and specifications may change without notice. Please consult ANA for all current information.

SPECIFICATIONS



PDS400S-6E1 400 cfm

| COMPRESSOR SPECIFICATIONS | |
|-----------------------------|---|
| Туре | Single-Stage, Oil Cooled, Screw Type |
| Free Air Delivery | 400 cfm |
| Working Pressure | 102 psig |
| Max. Working Pressure | 125 psig |
| Air Receiver Tank Capacity | 25.88 gal |
| Air Outlets | 1 x 2"; 2 x ¾" |
| Engine Coupling Type | Rubber coupling |
| Lubrication System Type | Forced lubrication by compressed air |
| Lubrication System Capacity | 10.6 gal. |
| Oil Cooler Type | Separate side-by-side oil cooler and radiator |
| ENGINE SPECIFICATIONS | |
| Model | Kubota V3800-T4F |
| Туре | Water-Cooled 4-Cycle, Direct-Injection, Turbocharged Air-to-Air Intercooled, EGR, DOC+DPF, SCR Tier 4F & CARB Compliant |
| Cylinders | 4 |
| Displacement | 230 cu.in. (3.769 L) |
| Horsepower | 108 hp (80.5 kw) |
| Low Idle | 1350 rpm |
| High Idle | 2600 / 2400-2700 rpm |
| Fuel Consumption | 4.62 gal./hr. |
| Fuel Capacity | 47.0 gal. |
| Def Tank Capacity | 5.3 gal. |
| Cooling System Capacity | 4.1 gal. |
| Oil Capacity | 3.4 gal. |
| Electrical System | 130F51x1 (12V) Maintenance-Free Battery |
| WEIGHTS AND DIMENSIONS | |
| Dry Weight | 3,550 lb. |
| Weight w/ Towing Frame | 3,975 lb. |
| Operating Weight | 4,012 lb. |
| LxWxH w/o Towing frame | 106" x 55" x 60" |
| LxWxH w/ Towing frame | 174" x 69" x 69" |
| OPERATING PARAMETERS | |
| Min. Ambient Temperature | 5° F |
| Max. Incline | 15° |
| Sound Level | 76 dBA |



Alliance North America

Phone: 562-450-3570

E-mail: sales@anacorp.com

www.anacorp.com

California: 12311 Industry St. • Garden Grove, CA 92841
Texas: 10440 Brockwood Road • Dallas, Texas 75238
South Carolina: 4220 S. Church St. • Roebuck, SC 29376

© COPYRIGHT 2020, ANA • 020420 AIRMAN is a trademark of HOKUETSU INDUSTRIES CO., LTD.

Features and specifications may change without notice. Please consult ANA for all current information.